


Ø 10.0 5x7 Dot Matrix Dual Color LED Display

4.0" (100.96mm) matrix height


● ABSOLUTE MAXIMUM RATINGS : (T_a=25°C)

PARAMETER	SR RED	RED ORANGE	GREEN	UNIT
Power Dissipation Per Seg	72	65	65	mW
Peak Forward Current Per Seg (1/10 Duty Cycle, 0.1ms Pulse Width)	125	100	100	mA
Continuous Forward Current Per Seg	30	25	25	mA
Derating Linear From 25°C Per Seg	0.42	0.33	0.33	mA/°C
Reverse Voltage Per Seg	5	5	5	v
Operating Tem Range	-35°C to + 85°C			
Storage Tem Range	-35°C to + 85°C			
Solder Tem 1/16 inch Below Seating Plane at 260°C for 3 seconds				

● PACKAGE DIMENSIONS



● INTERNAL CIRCUIT DIAGRAM




● ELECTRICAL/OPTICAL CHARACTERISTICS

PART NO.	COLOR	λ_p/λ_d (nm)	Half-Spectral Width($\Delta\lambda$)	Description	AVERAGE LUMINOUS INTENSITY			FORWARD VOLTAGE	
					Min.(mcd)	Typ.(mcd)	@ I _F (mA)	Typ.(V)	@ I _F (mA)
M402570EG...	RED ORANGE	632/622	35	CA	14.0	35.0	I _p =80mA 1/16 Duty	4	20
	GREEN	568/573	30		14.0	35.0		4.2	20
M402570SU...	SR RED	660/643	20	CA	22.0	55.0		4	20
	GREEN	568/570	30		18.0	45.0		4.2	20

Notes : These components are also available in :

- Low Current
- AllnGaP high intensity red,orange,yellow green,amber

Ø 10.0 5x7 Dot Matrix Dual Color LED Display




4.0" (100.96mm) matrix height


● ABSOLUTE MAXIMUM RATINGS : (Ta=25°C)

PARAMETER	SR RED	RED ORANGE	GREEN	UNIT
Power Dissipation Per Seg	72	65	65	mW
Peak Forward Current Per Seg (1/10 Duty Cycle, 0.1ms Pulse Width)	125	100	100	mA
Continuous Forward Current Per Seg Derating Linear From 25°C Per Seg	30 0.42	25 0.33	25 0.33	mA mA/°C
Reverse Voltage Per Seg	5	5	5	v
Operating Tem Range	-35°C to + 85°C			
Storage Tem Range	-35°C to + 85°C			
Solder Tem 1/16 inch Below Seating Plane at 260°C for 3 seconds				

● PACKAGE DIMENSIONS



● INTERNAL CIRCUIT DIAGRAM



● ELECTRICAL/OPTICAL CHARACTERISTICS

PART NO.	COLOR	λ_p/λ_d (nm)	Half-Spectral Width($\Delta\lambda$)	Description	AVERAGE LUMINOUS INTENSITY			FORWARD VOLTAGE	
					Min(mcd)	Typ.(mcd)	@ IF(mA)	Typ.(V)	@ IF(mA)
M404570EG...	RED ORANGE	632/622	35	CA	14.0	35.0	Ip=80mA 1/16 Duty	4	20
	GREEN	568/570	30		14.0	35.0		4.2	20
M404570SU...	SR RED	660/643	20	CA	22.0	55.0		3.6	20
	GREEN	568/570	30		18.0	45.0		4.2	20

Notes : These components are also available in :

- Low Current
- AllnGaP high intensity red,orange,yellow green,amber